

TACTILE COLOURMAX YELLOW STAINLESS STEEL (316)



TYPE	Tactile
RANGE	Warning Tactile
DESIGN	Classic Colourmax
MATERIAL	316 marine grade stainless steel
FINISH	Machined / Moulded
DIMENSIONS	OUTER DIA: 35mm TOP DIA: 25mm THICKNESS: 5mm SHAFT: M6mm x 18mm



FEATURES

Machined, concentric circle design on the horizontal face with a smooth outer edge

Tested for compliance with AS 1428.4

Tested for compliance with the NCC Section D clause 3.8 (TGSIs)

Tested for compliance with slip resistance requirements as detailed in HB 198

Backed by 2 year warranty

SLIP RESISTANCE TESTING

Important information: To determine a classification of a slip resistance rating, see Australian Standards Hand Book 198 (HB 198), an Introductory Guide to Slip Resistance of Pedestrian Materials. This document outlines the minimum ratings of a location and situation of a pedestrian surface.

TEST	Wet Pendulum Test — AS 4586 APPENDIX A
FOUR S 96 SLIDER	= 84 CLASS = P5
TRL 55 SLIDER	= 59 CLASS = P5

LUMINANCE TESTING

Important information: To determine a luminance contrast between a substrate and the DTAC TGSi node, see: AS 1428.4:2009. DTAC can test your substrate for luminance contrast to give you peace of mind that your DTAC project will be fully compliant to AS 1428.4.

TEST	Design for Access & Mobility — AS 1428.4 APPENDIX E
LUMINANCE REFLECTANCE RATING / WET	= 40.20
LUMINANCE REFLECTANCE RATING / DRY	= 38.60

DTAC PTY LTD
ABN 41 093 070 127

Unit 4, 11-12 Phillip Court
Port Melbourne Victoria
Australia 3207

PO Box 5059
South Melbourne Victoria
Australia 3205

T 1300 793 478
F 1300 780 628


estimating@dtac.com.au
www.dtac.com.au

© DTAC Pty Ltd 2018

TACTILE COLOURMAX YELLOW

INSTALLATION & APPLICATION

SUBSTRATE Stone / Masonry / Timber / Vinyl




CODE DT0400Y

FIXING Drill and pressure fit

NOTE Any thick substrate
where maximum hold is
required without chemical
anchoring

SUBSTRATE Vitrified Porcelain / Ceramics / Glass / Metals



CODE DT0400Y

FIXING Diamond core/pressure fit

NOTE Any thick substrate
where maximum hold is
required without chemical
anchoring