

TACTILE CLASSIC BRASS



TYPE	Tactile
RANGE	Warning Tactile
DESIGN	Classic
MATERIAL	Solid brass
FINISH	Machined
DIMENSIONS	OUTER DIA: 35mm TOP DIA: 25mm THICKNESS: 5mm SHAFT: M6mm x 18mm



FEATURES

Machined, concentric circle design on the horizontal face with a smooth outer edge

Tested for compliance with AS 1428.4

Tested for compliance with the NCC Section D clause 3.8 (TGSIs)

Tested for compliance with slip resistance requirements as detailed in HB 198

Backed by 2 year warranty

SLIP RESISTANCE TESTING

Important information: To determine a classification of a slip resistance rating, see Australian Standards Hand Book 198 (HB 198), an Introductory Guide to Slip Resistance of Pedestrian Materials. This document outlines the minimum ratings of a location and situation of a pedestrian surface.

TEST Wet Pendulum Test — AS 4586 APPENDIX A

FOUR S 96 SLIDER = 106 **CLASS** = P5

TRL 55 SLIDER = 83 **CLASS** = P5

TEST Wet/Barefoot Ramp Test — AS 4586 APPENDIX C

MEAN ANGLE OF INCLINATION = 27° **CLASS** = C

TEST Oil/Wet Ramp Test — AS 4586 APPENDIX D

CORRECTED MEAN OVERALL ACCEPTANCE ANGLE = 33° **CLASS** = R12

LUMINANCE TESTING

Important information: To determine a luminance contrast between a substrate and the DTAC TGSi node, see: AS 1428.4:2009. DTAC can test your substrate for luminance contrast to give you peace of mind that your DTAC project will be fully compliant to AS 1428.4.

TEST Design for Access & Mobility — AS 1428.4 APPENDIX E


LUMINANCE REFLECTANCE RATING / WET = 36.61

LUMINANCE REFLECTANCE RATING / DRY = 38.68

TACTILE CLASSIC

INSTALLATION & APPLICATION

SUBSTRATE Stone / Masonry / Timber / Vinyl




CODE DT0300

FIXING Drill and pressure fit

NOTE Any thick substrate where maximum hold is required without chemical anchoring


SUBSTRATE Vitrified Porcelain / Ceramics / Glass / Metals



CODE DT0300

FIXING Diamond core/pressure fit

NOTE Any thick substrate where maximum hold is required without chemical anchoring



CODE DT0301

FIXING Direct stick

NOTE Any thick or thin non drillable substrate