

EDGING RUGGED™ FIBRE REINFORCED POLYMER

P5
GRIP

TYPE	Edging
RANGE	Stair Edging
DESIGN	Rugged™
MATERIAL	Fibre Glass Reinforced Polymer
FINISH	Yellow or Black



FEATURES

Continuous band of hard wearing, fibre glass reinforced plastic extrusion

Available in exclusive premium quality angle profiles

Suitable for all stable finished outdoor or indoor surfaces and substrates

Designed to comply with AS 1428.1 Design for Access and Mobility Part 1: General Requirements for Access — New Building Work

Tested for compliance with slip resistance requirements as detailed in HB 198

Backed by 2 year warranty

NCC COMPLIANT

National Construction Code (NCC) compliant products are designed to comply with the NCC—and Disability (Access to Premises—Buildings) Standards to meet the deemed-to-satisfy-provisions

SLIP RESISTANCE TESTING

Important information: To determine a classification of a slip resistance rating, see Australian Standards Hand Book 198 (HB 198), an Introductory Guide to Slip Resistance of Pedestrian Materials. This document outlines the minimum ratings of a location and situation of a pedestrian surface.

TEST Wet Pendulum Test — AS 4586 APPENDIX A

FOUR S 96 SLIDER = 72 **CLASS** = P5

LUMINANCE TESTING

Important information: To determine a luminance contrast between a substrate and the DTAC EDGING, see: AS 1428.1:2009. DTAC can test your substrate for luminance contrast to give you peace of mind that your DTAC project will be fully compliant to AS 1428.1.

TEST Design for Access & Mobility — AS 1428.1 APPENDIX B

YELLOW

LUMINANCE REFLECTANCE RATING / WET = 39.5

LUMINANCE REFLECTANCE RATING / DRY = 36.9

BLACK

LUMINANCE REFLECTANCE RATING / WET = 6.6

LUMINANCE REFLECTANCE RATING / DRY = 7.6

DTAC PTY LTD
ABN 41 093 070 127

Unit 4, 11-12 Phillip Court
Port Melbourne Victoria
Australia 3207

PO Box 5059
South Melbourne Victoria
Australia 3205

PEMKO®

T 1300 793 478
F 1300 780 628


estimating@dtac.com.au
www.dtac.com.au

© DTAC Pty Ltd 2017

EDGING RUGGED™ FINISHES & SIZES

DESIGNER STAIR EDGING - AVAILABLE SIZES

YELLOW



CODE DEF0010Y

SIZE H10 x W70 x T3 - L1500

NCC COMPLIANT


BLACK



CODE DEF0010B

SIZE H10 x W70 x T3 - L1500

NCC COMPLIANT



CODE DEF0020Y

SIZE H10 x W70 x T3 - L1800

NCC COMPLIANT



CODE DEF0020B

SIZE H10 x W70 x T3 - L1800

NCC COMPLIANT

AVAILABLE FINISHES

YELLOW




BLACK



EDGING RUGGED™ INSTALLATION & APPLICATION


SUBSTRATE Stone / Masonry / Timber / Vinyl



FIXING Screw-fixed. Optional adhesive.

NCC COMPLIANT

SUBSTRATE Vitrified Porcelain / Ceramics / Glass / Metals



FIXING Screw-fixed. Optional adhesive.

NOTE Ensure grout line is discrete as illustrated

NCC COMPLIANT